

***** *** Network Configuration Page *** *****		Encryption Authentication		WSD Timeout1 [min]			
Product Information	Product Name	MB5100 series	TCP/IPv4 IP Address Subnet Mask Default Gateway	TCP/IPv6	LPD PrintingEnable		
	ROM Version	1.110			RAW PrintingEnable		
	Serial Number	AEMI			Bonjour Bonjour Service NameEnable Canon MB5100 series		
Wireless LAN	Enable		Link Local Address Link Local Prefix Length	LLMNR SNMP	Enable Enable		
MAC Address	74:38:B7:77:77:77						
Infrastructure	Enable		IPsec Security Protocol	Wired LAN MAC Address	DNS Server Auto		
	Connection	Inactive					
	SSID	BJNPSETUP	TCP/IPv4 IP Address Subnet Mask Default Gateway	Disables 74:BF:C0:C	Primary Server Secondary Server Proxy Server Proxy Address Proxy Port		
	Channel						
	Encryption	none	TCP/IPv6	Link Local Address Link Local Prefix Length	Cert. Fingerprt(SHA-1) Cert. Fingerprt(SHA-256)		
	WEP Key Length	Inactive					
	Authentication	none	Stateless Address1 Stateless Prefix Length1 Stateless Address2 Stateless Prefix Length2 Stateless Address3 Stateless Prefix Length3 Stateless Address4 Stateless Prefix Length4	Default Gateway1 Default Gateway2 Default Gateway3 Default Gateway4			
	Signal Strength	0[%]					
	TCP/IPv4	Enable	IPsec Security Protocol	Wired LAN DRX			
	IP Address						
	Subnet Mask		Other Settings	Printer Name Direct Conn. DevName			
	Default Gateway						
	TCP/IPv6	Enable	WSD Printing	Enable			
	Link Local Address						
	Link Local Prefix Length						
Direct Connection	Stateless Address1						
	Stateless Prefix Length1						
	Stateless Address2						
	Stateless Prefix Length2						
	Stateless Address3						
IPsec	Stateless Prefix Length3						
	Stateless Address4						
	Stateless Prefix Length4						
	Default Gateway1						
	Default Gateway2						
Security Protocol	Default Gateway3						
	Default Gateway4						
	IPsec	Inactive					
	Security Protocol						
	Direct Connection	Disable					
Connection	Connection						
	SSID						
	Password						
	Channel						