

P7P55D DELUXE DDR3 1600 Qualified Vendors List (QVL)										
Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Table(Bios)	Voltage	Eket support (A* B* C*)	
A-DATA	AD31600E001GMU	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	8-8-8-24(1333-9-9-9-24)	1.65-1.85	•	• •
A-DATA	AD31600F002GMU(XMP)	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	7-7-7-20(1333-9-9-9-24)	1.75-1.85	•	• •
CORSAIR	TR3X3G1600C8D(XMP)/Ver2.1	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	8-8-8-24(1601-8-8-8-24)	1.65	•	•
CORSAIR	TR3X3G1600C8D	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	8-8-8-24(1600-8-8-8-24)	1.65	•	•
CORSAIR	TR3X3G1600C9(XMP)/Ver1.1	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	9-9-9-24(1601-9-9-9-24)	1.65	•	•
CORSAIR	BoxP/N:TW3X4G1600C8DHXNV/(CM3X2G1600C8DHXNV)/Ver4.1	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	(1333-9-9-9-24)	1.80	•	• •
CORSAIR	TR3X8G1600C8D(XMP)/Ver2.1	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8-24(1601-8-8-8-24)	1.65	•	• •
CORSAIR	TR3X6G1600C8D	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8-24(1600-8-8-8-24)	1.65	•	• •
CORSAIR	TR3X8G1600C9(XMP)/Ver2.1	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1333-9-9-9-24)	1.65	•	• •
Crucial	BL12864BA1608.8SF8(XMP)	DDR3 1600	1024MB	SS	N/A	Heat-Sink Package	(1601-8-8-8-24)	1.8	•	• •
G.SKILL	F3-12800CL9D-2GBNQ	DDR3 1600	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	(1333-9-9-9-24)	1.6	•	• •
G.SKILL	F3-12800CL8T-6GBHK(XMP)	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8-21(1333-8-8-8-21)	1.6-1.65	•	• •
G.SKILL	F3-12800CL8T-6GBHX(XMP)	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8-21(1066-8-8-8-20)	1.6-1.65	•	• •
G.SKILL	F3-12800CL9T-6GBNQ	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1601-9-9-9-24)	1.5-1.6	•	• •
QEIL	GV34GB1600C8DC	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	8-8-8-28(1600-8-8-8-28)	1.6	•	• •
KINGMAX	FLD045F-B8K09-NAES	DDR3 1600	1024MB	SS	KINGMAX	KFB8FNGXF-ANX-12A	9(1600-9-8-8-28)	1.5	•	• •
KINGMAX	FLGE85F-B8K09-NEES	DDR3 1600	2048MB	DS	KINGMAX	KFB8FNGXF-ANX-12A	9(1600-9-8-8-28)	1.5	•	• •
KINGSTON	KHX12800D3LK3/3G(XMP)	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	1600-8-8-8-20	1.65	•	•
KINGSTON	KHX12800D3K3/2GX(XMP)	DDR3 1600	12288MB(Kit of 3)	DS	N/A	Heat-Sink Package	9(1066-9-9-9-24)		•	• •
KINGSTON	KHX12800D3K2/4G	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	9(1333-9-9-9-24)	1.9	•	• •
KINGSTON	KHX12800D3LK3/6GX(XMP)	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	(1066-8-8-8-20)	1.65	•	• •
OCZ	OC23P1600EB1G	DDR3 1600	1024MB	SS	N/A	Heat-Sink Package	7-6-6-24(1333-7-7-7-20)		•	•
OCZ	OC23G1600LV3GK	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	8-8-8(1066-7-7-7-20)	1.65	•	• •
OCZ	OC23P1600LV3GK	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	7-7-7(1066-7-7-7-20)	1.65	•	• •
OCZ	OC23P16004GK	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-7(1333-7-7-7-20)	1.9	•	•
OCZ	OC23P1600E4GK	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-6(1333-7-7-7-20)	1.8	•	
OCZ	OC23G1600LV6GK	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8(1066-7-7-7-20)	1.65	•	•
OCZ	OC23G1600LV6GK	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8(1066-7-7-7-16)	1.65	•	•
OCZ	OC23X1600LV6GK(XMP)	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8(1600-8-8-8-24)	1.65	•	• •
OCZ	OC23X1600LV6GK(XMP)	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8(1066-7-7-7-16)	1.65	•	• •
Super Talent	WB1600UX6GB(XMP)	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	1333-8-8-8-24		•	• •
Cell Shock	CS322271	DDR3 1600	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-7-14(1066-7-7-7-20)	1.7-1.9	•	• •
Elixir	M2F2G64CB8HA4N-DG	DDR3 1600	2048MB	DS	Elixir	N2CB1G80AN-DG	9(1333-9-9-9-28)		•	• •
Mushkin	996657	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-7-20		•	• •
Mushkin	996659(XMP)	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1333-9-9-9-24)	1.5-1.6	•	• •
Patriot	PVT33G1600ELK	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	9-9-9-24(1066-7-7-7-20)	1.65	•	• •
Patriot	PVS34G1600ELK	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	9-9-9-24(1066-7-7-7-20)	1.8	•	•
Patriot	PVS34G1600LLK(XMP)	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-7-20(1066-7-7-7-20)	1.9	•	•
Patriot	PVS34G1600LLKN	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-7-20(1066-7-7-7-20)	2.0	•	•
Patriot	PVT36G1600ELK	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1066-7-7-7-20)	1.65	•	• •
Patriot	PVT36G1600ELK	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1600-7-7-7-20)	1.65	•	• •
PQI	MFADR401PAD102(XMP)	DDR3 1600	2048MB	DS	SAMSUNG	K4B1G08460	1066-8-8-8-20		•	• •

6 Dimm :

- A* : Supports **one module** inserted in any slot as Single-channel memory configuration
- B* : Supports **one pair of modules** inserted into either the blue slots or the black slots as one pair of **Dual-channel** memory configuration
- C* : Supports **4 modules** inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the blue slots for better overlocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overlocking may operate at a lower frequency than the vendor-marked value.

P7P55 DELUXE Memory Qualified Vendors List (QVL)										
P7P55 DELUXE DDR3 1625 Qualified Vendors List (QVL)										
Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	Eket support (A* B* C*)	
KINGSTON	KHX13000D3LLK2/2GN(EPP)	DDR3 1625	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package		1.9	•	• •
KINGSTON	KHX13000D3LLK2/2GX(XMP)	DDR3 1625	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package		1.9	•	• •
KINGSTON	KHX13000D3LLK2/2GXN	DDR3 1625	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package		1.9	•	•

4 Dimm :

- A* : Supports **one module** inserted in any slot as Single-channel memory configuration
- B* : Supports **one pair of modules** inserted into either the blue slots or the black slots as one pair of **Dual-channel** memory configuration
- C* : Supports **4 modules** inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the blue slots for better overlocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overlocking may operate at a lower frequency than the vendor-marked value.

P7P55 DELUXE Memory Qualified Vendors List (QVL)										
P7P55 DELUXE DDR3 1800 Qualified Vendors List (QVL)										
Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	Eket support (A* B* C*)	
Apacer	78-0AGCD-CD2(XMP)	DDR3 1800	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	8-8-8-24(1800-8-8-8-24)	1.8	•	•
CORSAIR	BoxP/N:TW3X4G1800C8BDF/(CM3X2G1800C8D)/Ver4.1	DDR3 1800	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	8-8-8-24	1.80	•	•
KINGSTON	KHX14400D3/1G	DDR3 1800	1024MB	SS	N/A	Heat-Sink Package		1.9	•	•
KINGSTON	KHX14400D3K2/2GN(EPP)	DDR3 1800	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package		1.9	•	• •
KINGSTON	KHX14400D3K3/3GX(XMP)	DDR3 1800	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	1800-9-9-9-27	1.65	•	•
OCZ	OC23P18002GK	DDR3 1800	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	8		•	•
OCZ	OC23P18004GK	DDR3 1800	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	8	1.9	•	•
Transcend	TX1800KL-U-2GK(XMP)	DDR3 1800	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	8		•	•
Patriot	PVS32G1800LLKN(EPP)	DDR3 1800	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	8-8-8-20(1066-7-7-7-20)	1.9	•	

4 Dimm :

- **A***: Supports **one module** inserted in any slot as Single-channel memory configuration
- **B***: Supports **one pair of modules** inserted into either the blue slots or the black slots as one pair of **Dual-channel** memory configuration
- **C***: Supports **4 modules** inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the blue slots for better overlocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overlocking may operate at a lower frequency than the vendor-marked value.

P7P55 DELUXE Memory Qualified Vendors List (QVL)

P7P55 DELUXE DDR3 1866 Qualified Vendors List (QVL)

Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	cket support (A* B* C*)
CORSAIR	TR3X3G1866C9D(XMP)	DDR3 1866	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	9-9-9-24(1866-9-9-9-24)	1.65	• • •
CORSAIR	TR3X6G1866C9D	DDR3 1866	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1866-9-9-9-24)	1.65	• • •
KINGSTON	KHX14900D3K3G3GX(XMP)	DDR3 1866	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	9(1333-9-9-9-24)	1.65	• • •
OCZ	OC23RPR1866C9LV3GK	DDR3 1866	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	9-9-9(1066-7-7-7-20)	1.65	• • •
OCZ	OC23P1866C9LV6GK	DDR3 1866	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9(1066-7-7-7-20)	1.65	• • •
OCZ	OC23RPR1866C9LV6GK	DDR3 1866	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9(1066-7-7-7-20)	1.65	• • •
Super Talent	W1866UX2GB(XMP)	DDR3 1866	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	8-8-8-24(1333-9-9-9-24)	1.9	• • •
Patriot	PVS32G1866LLK(XMP)	DDR3 1866	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	8-8-8-24(1066-7-7-7-20)	1.9	• • •
Patriot	PVS32G1866LLK(XMP)	DDR3 1866	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	8-8-8-24(1866-8-8-8-24)	1.9	• • •

4 Dimm :

- **A***: Supports **one module** inserted in any slot as Single-channel memory configuration
- **B***: Supports **one pair of modules** inserted into either the blue slots or the black slots as one pair of **Dual-channel** memory configuration
- **C***: Supports **4 modules** inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the blue slots for better overlocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overlocking may operate at a lower frequency than the vendor-marked value.

P7P55 DELUXE Memory Qualified Vendors List (QVL)

P7P55 DELUXE DDR3 2000 Qualified Vendors List (QVL)

Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	cket support (A* B* C*)
Apacer	78.0AGCQ.CB2(XMP)	DDR3 2000	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	9-9-9-27(1066-8-8-8-20)	2	• • •
Crucial	BL12864BE2009.85FB3(EPP)	DDR3 2000	1024MB	SS	N/A	Heat-Sink Package	9-9-9-28(1333-9-9-9-24)	2	• • •
G.SKILL	F3-16000CL7T-6GBPS(XMP)	DDR3 2000	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	7-8-7-20(1066-8-8-8-20)	1.65	• • •
G.SKILL	F3-16000CL9T-6GBPS(XMP)	DDR3 2000	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1066-8-8-8-20)	1.65	• • •
KINGSTON	KHX16000D3K2/2GN(EPP)	DDR3 2000	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package		2.0	• • •
KINGSTON	KHX16000D3K3G3GX(XMP)	DDR3 2000	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	9(1333-9-9-9-24)	1.65	• • •
KINGSTON	KHX16000D3ULT1K3/6GX(XMP)	DDR3 2000	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8(1066-8-8-8-20)	1.65	• • •
KINGSTON	KHX16000D3T1K3/6GX(XMP)	DDR3 2000	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9(1066-8-8-8-20)	1.65	• • •
OCZ	OC23FXT20002GK	DDR3 2000	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	8	1.9	• • •
OCZ	OC23P20002GK(EPP)	DDR3 2000	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	9	1.9	• • •
OCZ	OC23P2000EB2GK	DDR3 2000	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	9-8-8(1066-8-7-7-20)	1.8	• • •
Gingie	9CAASS37AZZ01D1	DDR3 2000	2048MB	DS	N/A	Heat-Sink Package	9-9-9-24	1.9	• • •
Patriot	PVS32G2000LLKN	DDR3 2000	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	9-9-9-24(1066-7-7-7-20)	2	• • •

4 Dimm :

- **A***: Supports **one module** inserted in any slot as Single-channel memory configuration
- **B***: Supports **one pair of modules** inserted into either the blue slots or the black slots as one pair of **Dual-channel** memory configuration
- **C***: Supports **4 modules** inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the blue slots for better overlocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overlocking may operate at a lower frequency than the vendor-marked value.